



## 尼龍紮線帶

### 功能特性

- 材質：採用 UL 合格之 NYLON 66 (本色) 製成，防火等級 94 V - 2，不易老化，承受力強。
- 顏色：標準色為白色，另備有黑色，特殊顏色歡迎訂做。



### 電器規格說明

型號	長		寬 mm	最大束線徑 mm	承受力		包裝
	mm	inch			lbs	kgs	
CV-060B	83.7	2 1/2"	2.4	12	18	8	每包 100 pcs
CV-075B	75	3"	2.4	18	18	8	每包 100 pcs
CV-080B	80	3 1/8"	2.5	19	18	8	每包 100 pcs
CV-094B	96	3 3/4"	2.5	23	18	8	每包 100 pcs
CV-100B	100	4"	2.5	25	18	8	每包 100 pcs
CV-120SB	120	4 3/4"	2.5	30	18	8	每包 100 pcs
CV-120B	120	4 3/4"	3.2	30	40	18	每包 100 pcs
CV-120LB	120	4 3/4"	4.8	30	50	22	每包 100 pcs
CV-120LLB	120	4 3/4"	7.6	30	120	55	每包 100 pcs
CV-140SB	142	5 1/2"	2.5	35	18	8	每包 100 pcs
CV-140B	142	5 1/2"	3.2	35	40	18	每包 100 pcs
CV-150B	150	6"	3.6	39	40	18	每包 100 pcs
CV-150SB	155	6 1/8"	2.5	39	18	8	每包 100 pcs
CV-150LB	150	6"	7.6	39	120	55	每包 100 pcs
CV-160LB	160	6 1/4"	4.8	42	50	22	每包 100 pcs
CV-165B	165	6 1/2"	2.5	44	18	8	每包 100 pcs
CV-180B	180	7"	3.6	49	40	18	每包 100 pcs
CV-190B	190	7 1/2"	4.8	52	50	22	每包 100 pcs
CV-200MB	203	8"	2.5	55	18	8	每包 100 pcs
CV-200SB	203	8"	3.2	55	40	18	每包 100 pcs
CV-200AB	203	8"	3.6	55	40	18	每包 100 pcs
CV-200B	203	8"	4.6	55	50	22	每包 100 pcs
CV-200LB	203	8"	7.6	55	120	55	每包 100 pcs
CV-240LB	240	9 7/16"	7.6	66	120	55	每包 100 pcs
CV-250MB	250	10"	3	74	40	18	每包 100 pcs
CV-250B	250	10"	4.8	74	50	22	每包 100 pcs
CV-265B	265	10 1/2"	3.6	78	40	18	每包 100 pcs
CV-280B	280	11"	4.8	81	50	22	每包 100 pcs
CV-280LB	280	11"	7.6	78	120	55	每包 100 pcs
CV-292B	292	11 1/2"	3.6	85	40	18	每包 100 pcs
CV-300SB	300	11 5/8"	4.8	85	50	22	每包 100 pcs
CV-300B	300	11 7/8"	7.6	88	120	55	每包 100 pcs
CV-310B	310	12"	4.8	89	50	22	每包 100 pcs
CV-330B	330	13"	3.6	96	40	18	每包 100 pcs
CV-340B	340	13 1/2"	7.6	99	120	55	每包 100 pcs
CV-368SB	368	14 1/2"	3.6	102	40	18	每包 100 pcs